



symbol	description	quantity
BV1	hand ball valve G1/4	3
BV2	hand ball valve G3/8	3
F4	Gas filter , PS= 100 bar , 25 micron	1
F2	Gas filter , PS= 350 bar , 1 micron	2
HE3	CNG/H2O heat exchanger, PS=100 bar	1
HE4	coaxial pipes heat exchanger diam 35mm (PN160) for H2O and 20mm (PN320) for CH4	4
PG2	pressure gauge: 250 bar	2
PG5	pressure gauge: 100 bar	1
PT1	pressure transducer: 0 - 250 bar	4
PV3	carbon steel ball valve with double acting pneumatic actuator, 2 ways, DN20, PN315	1
PV5	carbon steel ball valve with double acting pneumatic actuator, 2 ways, DN32, PN 64	1
PV6	carbon steel ball valve with double acting pneumatic actuator, 2 ways, DN25, PN 315	2
SV5	calibrated safety valve 90 bar, inlet DN20, discharge DN 25	1
SV3	calibrated safety valve 242 bar, inlet DN20, discharge DN 25	2
TC	collar thermocouple	3
△	connection to vent	

E' vietato consegnare a terzi o riprodurre questo documento. L'utente si assume la responsabilita' di verificare l'accuratezza delle informazioni contenute in questo documento senza autorizzazione. Ogni infrazione comporta il risarcimento dei danni subiti. Sono riservati tutti i diritti derivanti dalla concessione di brevetti per invenzioni, di modelli industriali di utilita' e di disegni o modelli. (UNI ISO 1:6016)

M.T.M. s.r.l.
 SOCIETA' UNIPERSONALE
 Via La Morra 1 - 12062 -
 Cherasco (Cn), Italy
 Tel. +39 0172 488681
 Fax +39 0172 593113
 Fax +39 0172 488237
 http://www.brc.it
 e-mail: r&s@brc.it



REV.	DATA	MODIFICHE			FIRMA
Titolo/Title :		P&I compressor			
Item n°:		W132-013			
Scala/ scale:	Disegnatore :	Data :	Firma :	Sostituisce il/ Replaces:	
	M.Sartirano	15/02/07			
	Verificatore :	Data :	Firma :	Sostituito da/ Replaced by:	
	M.Galletta	16/02/07			
Formato :	Approvatore :	Data :	Firma :	Tavola/Sheet:	
A3	P.Abellonio	16/02/07		1/1	